



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.3751$   $y=0.3725$   $u'=0.2233$   $v'=0.4989$   
 CCT=4119K (Duv=-0.0004) Dominant WL:Ld =578.8nm Purity=24.4%  
 Peak WL:Lp=632.0nm FWHM=208.0nm  
 Render Index:Ra=96.3 Render Index:AvgR =96.2  
 R1 =98 R2 =98 R3 =94 R4 =93 R5 =98 R6 =98 R7 =96  
 R8 =95 R9 =96 R10=95 R11=92 R12=95 R13=99 R14=96 R15=98

### Photometric & Radiometric Parameters

Flux=200.7 lm Eff.:71.00 lm/W Fe=758.3 mW

### Electrical parameters

V=24.00 V I=0.1178 A P=2.827 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_4000K

Status: Integral T = 74 ms Ip = 50151 (77%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-FS-2403-12022-4095-SP005 Number:4  
 Test By:\*\* Date:2020-06-29 13:36:07  
 Temperature:23Deg Humidity:55%  
 Manufacturer:  
 Assessor:damin DeviceSN:

## TM30

