



Colorimetric Parameters

Chromaticity Coordinate: $x=0.3236$ $y=0.3339$ $u'=0.2035$ $v'=0.4725$
 CCT=5920K (Duv=0.0004) Dominant WL:Ld =3.4nm Purity=0.7%
 Peak WL:Lp=446.8nm FWHM=262.4nm
 Render Index:Ra=95.6 Render Index:AvgR =95.6
 R1 =99 R2 =97 R3 =93 R4 =92 R5 =98 R6 =97 R7 =94
 R8 =95 R9 =99 R10=92 R11=92 R12=94 R13=99 R14=96 R15=97

Photometric & Radiometric Parameters

Flux=341.3 lm Eff.:72.57 lm/W Fe=1.324 W

Electrical parameters

V=24.00 V I=0.1960 A P=4.704 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_5700K

Status: Integral T = 50 ms Ip = 49785 (76%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-FS-2405-12022-5795-SP005Number:19
 Test By:** Date:2020-06-12 17:28:27
 Temperature:23Deg Humidity:55%
 Manufacturer: Remarks:
 Assessor:damin DevideSN:

TM30

