



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.5053$   $y=0.4195$   $u'=0.2878$   $v'=0.5376$   
 CCT=2232K (Duv=0.0013) Dominant WL:Ld =586.6nm Purity=77.6%  
 Peak WL:Lp=651.6nm FWHM=131.0nm  
 Render Index:Ra=97.5 Render Index:AvgR =97.2  
 R1 =98 R2 =100 R3 =96 R4 =94 R5 =97 R6 =98 R7 =99  
 R8 =99 R9 =97 R10=99 R11=89 R12=99 R13=98 R14=96 R15=99

### Photometric & Radiometric Parameters

Flux=278.2 lm Eff.:62.86 lm/W Fe=1.290 W

### Electrical parameters

V=24.00 V I=0.1844 A P=4.425 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 31 ms Ip = 48682 (74%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-HD-2404-70022-2295-SP005 Number:1  
 Test By:\*\*\* Date:2020-06-23 10:40:06  
 Temperature:23Deg Humidity:55%  
 Manufacturer:  
 Assessor:damin DeviceSN:

## TM30

