



### Colorimetric Parameters

Chromaticity Coordinate: x=0.4403 y=0.4052/u'=0.2522 v'=0.5223  
 CCT=2954K (Duv=0.0000) Dominant WL:Ld =583.0nm Purity=53.8%  
 Peak WL:Lp=646.2nm FWHM=188.9nm  
 Render Index:Ra=96.9 Render Index:AvgR =96.4  
 R1 =100 R2 =98 R3 =95 R4 =94 R5 =98 R6 =98 R7 =96  
 R8 =97 R9 =97 R10=95 R11=92 R12=92 R13=99 R14=97 R15=99

### Photometric & Radiometric Parameters

Flux=294.9 lm Eff.:70.02 lm/W Fe=1.203 W

### Electrical parameters

V=24.00 V I=0.1755 A P=4.212 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 40 ms Ip = 49282 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-HD-2404-70022-3095-SP005 Number:3  
 Test By:\*\*\* Date:2020-06-23 10:44:52  
 Temperature:23Deg Humidity:55%  
 Manufacturer:  
 Assessor:damin DeviceSN:

## TM30

