



Colorimetric Parameters

Chromaticity Coordinate: $x=0.3869$ $y=0.3854$ $u'=0.2259$ $v'=0.5063$
 CCT=3895K (Duv=0.0022) Dominant WL:Ld =578.4nm Purity=31.8%
 Peak WL:Lp=449.5nm FWHM=16.9nm
 Render Index:Ra=98.2 Render Index:AvgR =97.4
 R1 =99 R2 =99 R3 =98 R4 =96 R5 =99 R6 =99 R7 =98
 R8 =99 R9 =99 R10=99 R11=92 R12=88 R13=99 R14=99 R15=99

Photometric & Radiometric Parameters

Flux=367.0 lm Eff.:84.07 lm/W Fe=1.418 W

Electrical parameters

V=24.00 V I=0.1819 A P=4.365 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_4000K

Status: Integral T = 39 ms Ip = 47943 (73%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-HD-2404-70022-4095-SP005 Number:5
 Test By:*** Date:2020-06-23 10:48:00
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin DeviceSN:

TM30

