



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4373$ $y=0.4031$ / $u'=0.2512$ $v'=0.5210$
 CCT=2986K (Duv=-0.0004) Dominant WL:Ld =583.0nm Purity=52.2%
 Peak WL:Lp=643.0nm FWHM=191.2nm
 Render Index:Ra=96.9 Render Index:AvgR =96.3
 R1 =100 R2 =98 R3 =95 R4 =94 R5 =98 R6 =97 R7 =96
 R8 =97 R9 =96 R10=95 R11=92 R12=90 R13=99 R14=97 R15=99

Photometric & Radiometric Parameters

Flux=348.8 lm Eff.:70.70 lm/W Fe=1.415 W

Electrical parameters

V=24.00 V I=0.2056 A P=4.934 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 34 ms Ip = 48948 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-HD-2405-70022-3095-SP005 Number:2
 Test By:*** Date:2020-06-29 13:32:33
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin DeviceSN:

TM30

