



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.3995$   $y=0.3745$  /  $u'=0.2387$   $v'=0.5034$   
 CCT=3494K (Duv=-0.0060) Dominant WL:  $L_d = 584.0\text{nm}$  Purity=32.3%  
 Peak WL:  $L_p=610.5\text{nm}$  FWHM=152.4nm  
 Render Index:  $R_a=93.3$  Render Index:  $AvgR = 90.3$   
 R1 =96 R2 =98 R3 =97 R4 =94 R5 =95 R6 =94 R7 =90  
 R8 =82 R9 =58 R10=93 R11=94 R12=74 R13=98 R14=97 R15=93

### Photometric & Radiometric Parameters

Flux=230.9 lm Eff.:71.16 lm/W  $F_e=756.7$  mW

### Electrical parameters

V=24.00 V I=0.1352 A P=3.245 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3500K

Status: Integral T = 50 ms  $I_p = 47612$  (73%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-SE-2403-12022-3595-SP005 Number:20  
 Test By:\*\*\* Date:2020-06-12 17:30:45  
 Temperature:23Deg Humidity:55%  
 Manufacturer: Remarks:  
 Assessor:damin

## TM30

