



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4406$ $y=0.4005$ / $u'=0.2545$ $v'=0.5205$
 CCT=2909K (Duv=-0.0019) Dominant WL:Ld =583.9nm Purity=52.4%
 Peak WL:Lp=632.9nm FWHM=125.0nm
 Render Index:Ra=97.5 Render Index:AvgR =96.7
 R1 =97 R2 =99 R3 =97 R4 =96 R5 =97 R6 =96 R7 =99
 R8 =99 R9 =98 R10=99 R11=93 R12=88 R13=97 R14=97 R15=98

Photometric & Radiometric Parameters

Flux=449.8 lm Eff.:85.12 lm/W Fe=1.722 W

Electrical parameters

V=24.00 V I=0.2202 A P=5.284 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 21 ms Ip = 49559 (76%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-SW-2405-24022-3095-SP005 Number:7
 Test By:*** Date:2020-06-29 13:41:57
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin

TM30

