



## Colorimetric Parameters

Chromaticity Coordinate:  $x=0.5058$   $y=0.4190$   $u'=0.2883$   $v'=0.5374$

CCT=2224K (Duv=0.0012) Dominant WL:Ld =586.7nm Purity=77.6%

Peak WL:Lp=650.5nm FWHM=130.6nm

Render Index:Ra=97.3 Render Index:AvgR =96.9

R1 =98 R2 =100 R3 =96 R4 =94 R5 =97 R6 =98 R7 =98

R8 =99 R9 =97 R10=99 R11=88 R12=97 R13=98 R14=97 R15=99

## Photometric & Radiometric Parameters

Flux=216.4 lm Eff.:56.97 lm/W Fe=1.005 W

## Electrical parameters

V=24.00 V I=0.1583 A P=3.799 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 39 ms Ip = 47864 (73%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-US-2403-23822-2295-SP005 Number:7

Test By:

Date:2020-06-24 14:35:11

Temperature:23Deg

Humidity:55%

Manufacturer:

Assessor:damin

# TM30

