



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4784$ $y=0.4116$ / $u'=0.2741$ $v'=0.5306$
 CCT=2468K (Duv=-0.0008) Dominant WL:Ld =585.7nm Purity=67.2%
 Peak WL:Lp=648.1nm FWHM=144.0nm
 Render Index:Ra=97.1 Render Index:AvgR =96.9
 R1 =99 R2 =99 R3 =95 R4 =94 R5 =97 R6 =99 R7 =97
 R8 =98 R9 =97 R10=98 R11=90 R12=98 R13=99 R14=96 R15=99

Photometric & Radiometric Parameters

Flux=224.4 lm Eff.:62.04 lm/W Fe=989.5 mW

Electrical parameters

V=24.00 V I=0.1507 A P=3.616 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 43 ms Ip = 48632 (74%)
 Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-US-2403-23822-2595-SP005 Number:3
 Test By: Date:2020-06-24 14:26:04
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin

TM30

