



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.3830$   $y=0.3820$  /  $u'=0.2247$   $v'=0.5043$   
 CCT=3970K (Duv=0.0017) Dominant WL:Ld =578.3nm Purity=29.6%  
 Peak WL:Lp=448.8nm FWHM=18.3nm  
 Render Index:Ra=97.8 Render Index:AvgR =96.6  
 R1 =99 R2 =98 R3 =97 R4 =96 R5 =99 R6 =97 R7 =98  
 R8 =98 R9 =95 R10=97 R11=93 R12=87 R13=99 R14=98 R15=98

### Photometric & Radiometric Parameters

Flux=298.6 lm Eff.:79.25 lm/W Fe=1.138 W

### Electrical parameters

V=24.00 V I=0.1570 A P=3.768 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_4000K

Status: Integral T = 50 ms Ip = 49453 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-US-2403-23822-4095-SP005 Number:4  
 Test By: Date:2020-06-24 14:27:57  
 Temperature:23Deg Humidity:55%  
 Manufacturer:  
 Assessor:damin

# TM30

